

316 stainless steel flexible hose **Series 601, 602, 604, and 605**

4

Description
Series 601 hoses are constructed of 1/4" I.D. Teflon® lined stainless steel braid, rated for 3000 psig. The 601 hoses are fitted with 1/4" NPT brass end connections; they make excellent economical manifold pigtails. The 602 hoses are fitted with 1/4" NPT stainless steel end connections.
The Series 604 hoses are constructed of double braided stainless steel, fitted with stainless steel 1/4" NPT end connections, rated for 3000 psig, and cleaned for oxygen service.



Special Hoses
We can provide any of the hoses on this page in different lengths and with a wide variety of end fittings.

Series 601 and 602
<ul style="list-style-type: none"> 1/4" I.D. Teflon® lined 316 stainless steel braided hose Rated for 3000 psig 601 1/4" NPT female x 1/4" NPT female 601M 1/4" NPT male x 1/4" NPT male 601MF 1/4" NPT male x 1/4" NPT female 602 1/4" NPT female x 1/4" NPT female 602M 1/4" NPT male x 1/4" NPT male 602MF 1/4" NPT male x 1/4" NPT female Cleaned for oxygen service

Series 604 and 605
<ul style="list-style-type: none"> 1/4" I.D. 316 stainless steel double braided hose (605 Series has protective outer armor to provide greater safety and kink resistance.) Rated for 3000 psig 1/4" NPT female or male stainless steel end connections Cleaned for oxygen service

Ordering Information					
Model	Length	Model	Length	Model	Length
601-2	2.0 feet	602-3	3.0 feet	604-6	6.0 feet
601M-2	2.0 feet	602M-3	3.0 feet	604M-6	6.0 feet
601MF-2	2.0 feet	602MF-3	3.0 feet	604MF-6	6.0 feet
601-3	3.0 feet	602-6	6.0 feet	605-2	2.0 feet
601M-3	3.0 feet	602M-6	6.0 feet	605M-2	2.0 feet
601MF-3	3.0 feet	602MF-6	6.0 feet	605MF-2	2.0 feet
601-6	6.0 feet	604-2	2.0 feet	605-3	3.0 feet
601M-6	6.0 feet	604M-2	2.0 feet	605M-3	3.0 feet
601MF-6	6.0 feet	604MF-2	2.0 feet	605MF-3	3.0 feet
602-2	2.0 feet	604-3	3.0 feet	605-6	6.0 feet
602M-2	2.0 feet	604M-3	3.0 feet	605M-6	6.0 feet
602MF-2	2.0 feet	604MF-3	3.0 feet	605MF-6	6.0 feet

Cryogenic transfer hoses **Series 607C**

- 1/2" I.D. 316 stainless steel double braided hose with protective outer armor to provide greater safety and kink resistance
- Rated for 2150 psig
- 1/2" 45° flare female stainless steel connections (CGA 295) or 5/8" 45° flare (CGA 440) for oxygen
- Cleaned for oxygen service



Special Hoses
We can provide any of the hoses on this page in different lengths and with a wide variety of end fittings.

Ordering Information		
Model	Length	Model
607C-4	for nitrogen and argon	4.0 feet
607C-6	for nitrogen and argon	6.0 feet
607C-4-440	for oxygen	4.0 feet
607C-6-6440	for oxygen	6.0 feet